



More information on the website  
[radwag.com/en/info,w1,l36](http://radwag.com/en/info,w1,l36)

# C32.0,6.D2 Multifunctional Scale



## Functions



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit measurement



Statistics



IR sensors



Under-pan weighing



GLP Procedures



Replaceable unit



ALIBI Memory

## Datasheet

### Metrological parameters

Maximum capacity [Max]	0,6 kg
Minimum load	4 g
Readability [d]	0,2 g
Tare range	-0,6 kg
OIML Class	III

### Physical parameters

Display	5" graphic colour
---------	-------------------

Physical parameters	
Weighing pan dimensions	195×195 mm
Packaging dimensions	490×300×150 mm
Net weight	3,4 kg
Gross weight	4,3 kg
Construction	
Communication interface	
Communication interface	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters	
Power supply	100 ÷ 240 V AC 50 / 60 Hz and battery*
Power consumption max.	10 W
Operation time on batteries	operation time up to 5 h
Environmental conditions	
Operating temperature	-10 ÷ +40 °C
Weighing pan material	stainless steel AISI304



## Accessories

Cigarette lighter receptacle power supply cables  
Barcode scanners  
Receipt Printer  
Displays

Keypad, external switches  
Stands, wall mounting kits and mounting brackets  
RS 232, RS 485 cables  
RS 232 cables (scale - EPSON printer)

## Software

RAD-KEY  
RADWAG Connect  
R-LAB  
E2R System

LabVIEW Driver  
Label Editor R02  
RADWAG Development Studio  
R.Barcode

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.